

# COATED FABRIC 1410

Saint-Gobain Performance Plastics COHRIlastic® Coated Fabric 1410 is a silicone rubber dispersion-coated nylon fabric, developed to meet the requirements of Boeing Materials Specification BMS-1-17D, type I and II, Grade B. CF 1410 is suitable for continuous exposure to weather. It is not recommended for use with hydrocarbon fuels, oils or lubricants.

## Typical Physical Properties\*

Property	Units	Value
Weight	Oz./Yd. <sup>2</sup> Avg.	7
Overall Thickness	Inches	0.009
Burst Strength	Lbs./Min.	400
Tear Strength (As received)	Lbs./Min.	80
Tear Strength (After abrasion)	Lbs./Min.	35
Air Permeability	CFM/Sq. Ft., Max	2.0
Stiffness (Type I)	mm, Max	250
Stiffness (Type II)	mm, Max	100
Color		White

\*Values are typical properties and should not be used for writing specifications.

## Availability

CF 1410 is sold by the yard in continuous lengths, 36" wide.

CF 1410 is a custom product. Please contact customer service for minimum order quantities, price and delivery.

**Limited Warranty:** For a period of 6 months from the date of first sale, Saint-Gobain Performance Plastics Corporation warrants this product(s) to be free from defects in manufacturing. Our only obligation will be to provide replacement product for any portion proving defective, or at our option, to refund the purchase price thereof. User assumes all other risks, if any, including the risk of injury, loss or damage, whether direct or consequential, arising out of the use, misuse, or inability to use this product(s). SAINT-GOBAIN PERFORMANCE PLASTICS DISCLAIMS ANY AND ALL OTHER WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE.

**NOTE:** Saint-Gobain Performance Plastics Corporation does not assume any responsibility or liability for any advice furnished by it, or for the performance or results of any installation or use of the product(s) or of any final product into which the product(s) may be incorporated by the purchaser and/or user. The purchaser and/or user should perform its own tests to determine the suitability and fitness of the product(s) for the particular purpose desired in any given situation.

## Application Advantages

- Resistant to creasing and corrosion.
- Resistant to wear and tear.

**Saint-Gobain Performance Plastics Corporation**  
14 McCaffrey St.  
Hoosick Falls, New York 12090-0320  
**Customer Service: (800) 962-2666**  
Tel: (518) 686-7301  
Fax: (800) 562-8479, (518) 686-4840

[www.fff.saint-gobain.com](http://www.fff.saint-gobain.com)

COHRIlastic is a registered trademark.  
©2005 Saint-Gobain Performance Plastics Corporation  
AFF-1478-PDF-1205-SGCS