

NORTON®

EXTRUDED PTFE FILM R128 AND R129

R128 and R129 Premium extruded PTFE Films are designed for use as the primary insulation for high temperature wire and cable and wall construction for convoluted hose. They are available in white and natural as R128 and in many colors as R129. These products are used in the most demanding applications requiring high performance and close tolerances. They are easily applied with industry tape wrapping and sintering equipment and provide excellent dielectric strength, and thermal and chemical resistance. R128 and R129 meet the requirements of component insulation to MIL-W-16878/4A, 7139B, MIL-W-22759B and NAS703.

Typical Properties

Total Thickness	Specific Gravity	Longitudinal Tensile	Elongation	Width Tensile	Approx. Yield
in./mm	grams/cc	psi	percent	psi	sq. ft./lb.
.002 / .051	1.6	2500	75	250	60.2
.003 / .076	1.6	2300	125	275	40.1
.004 / .102	1.6	2200	125	350	30.1
.005 / .127	1.6	1900	150	350	24.1
.010 / .254	1.6	1000	300	375	12.0

Values shown are typical and should not be used for specifications. All data is subject to change without notice. In all instances the user shall determine the suitability in any given application.

Availability

R128 and R129 are available on 3" ID cores, in flat pad or traverse wind configuration. Customized packaging and products are available. Certification and test reports are available upon request.

Other Products

Saint-Gobain manufactures a complete line of high performance PTFE films, fabrics and pressure sensitive tapes, for use in the wire and cable, and convoluted hose industries.

- **Premium, High Temperature Insulation**
- **Colors Available**
- **Excellent Service and Availability**
- **Customized Products**

To place an order call Customer Service
toll free: (800) 962-2666, Fax: (800) 526-8479

Limited Warranty: For a period of 6 months from the date of first sale, Saint-Gobain Performance Plastics Corporation warrants this product(s) to be free from defects in manufacturing. Our only obligation will be to provide replacement product for any portion proving defective, or at our option, to refund the purchase price thereof. User assumes all other risks, if any, including the risk of injury, loss or damage, whether direct or consequential, arising out of the use, misuse, or inability to use this product(s). SAINT-GOBAIN PERFORMANCE PLASTICS DISCLAIMS ANY AND ALL OTHER WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE.

NOTE: Saint-Gobain Performance Plastics Corporation does not assume any responsibility or liability for any advice furnished by it, or for the performance or results of any installation or use of the product(s) or of any final product into which the product(s) may be incorporated by the purchaser and/or user. The purchaser and/or user should perform its own tests to determine the suitability and fitness of the product(s) for the particular purpose desired in any given situation.

Saint-Gobain Performance Plastics Corporation
P.O. Box 320
McCaffrey Street
Hoosick Falls, NY 12090
Customer Service: (800) 962-2666
Tel: (518) 686-7301
Fax: (518) 686-4840
www.fff.saint-gobain.com

NORTON® is a registered trademark.

©2004 Saint-Gobain Performance Plastics Corporation
AFF-1302-PDF-0804-SGCS