# **ThermaCool**®

# Thermal Interface Materials

# ThermaCool® C690 Series Thermally Conductive Graphite Tape

**ThermaCool® C690 Series** is comprised of flexible graphite film, coated on one side with 0.025mm thick thermally conductive acrylic pressure-sensitive adhesive.

# Features/Benefits

- Graphite film spreads heat evenly to allow for maximum heat sink potential at low pressures
- Soft graphite material conforms readily to surface imperfections to improve thermal transfer
- One-sided adhesive construction allows for easy rework, replacement, or upgrade of components
- Pressure-sensitive adhesive tape can be pre-applied to a heat sink to minimize assembly costs

# **Typical Properties**

Property	C695	C6910	Test Method
Colour	Metallic Black	Metallic Black	_
Thickness mm (mils)	0.152 (6.0)	0.279 (11.0)	ASTM D1000
Tensile Strength MPa (psi)	3.45 (500)	3.45 (500)	ASTM D1000
Thermal Conductivity W/m <sup>-1</sup> K <sup>-1</sup>	4.0	2.4 with adhesive 5.0 uncoated	ASTM E1530
Thermal Impedance @ 10 psi °C in.²/W	0.10	0.10	ASTM E1530
Operating Temperature °C	-29 to +149	-29 to +149	_
Adhesion to Aluminum N/cm (oz./in.)	3.3 (30)	3.3 (30)	ASTM D1000
Adhesion to Liner N/cm (oz./in.)	0.9 (8)	0.9 (8)	ASTM D1000

# **Applications**

- Bonding components to heat sinks where electrical isolation is not a concern
- Creating electrically conductive surface on electrically isolating materials
- Heat spreading capabilities make C690 tapes ideal for bonding multiple components to a single heat sink

Availability—Available in slit-rolls up to 610mm wide.

Saint-Gobain Performance Plastics sales, fabrication and distribution facilities are situated at the following locations:

## Ireland

Tel: +353 65 9080170 Fax: +353 65 9080177

Email: aff.europe@saint-gobain.com

#### Germany

Tel: +49 221 9714080 Fax: +49 221 97140835

Email: aff.germany@saint-gobain.com

#### France

Tel: +33 4 68635353 Fax: +33 4 68632646

Email: aff.france@saint-gobain.com

#### IJК

Tel: +44 1706 746900 Fax: +44 1706 746991

Email: aff.uk@saint-gobain.com

#### talv

Tel: +39 041 5350203 Fax: +39 041 2668908 Email: aff.italy@saint-gobain.com

# Spain

Tel: +34 96 1536170 Fax: +34 96 1536170

Email: aff.spain@saint-gobain.com

### www.fff.saint-gobain.com

ThermaCool® is a registered trademark.

The data listed herein fall within the normal range of product properties for the products described, but they should not be used to establish specification limits nor used alone as the basis of design. SAINT-GOBAIN assumes no obligation or liability for any advice furnished by it or for results obtained to these products. All such advice is provided gratis and Buyer assumes sole responsibility for results obtained in reliance thereon. SAINT-GOBAIN warrants that the material itself does not knowingly infringe any patent, but no license is implied nor is any further warranty made.

©2005 Saint-Gobain Performance Plastics Corporation AFF-1273E-PDF-0705-SGCS

